



apcotex industries limited

AN ISO 9001: 2008 COMPANY

APCOTEX AC 2550

Apcotex AC 2550 is specialty Pure Acrylic copolymer dispersion designed for premium quality emulsion paints for interior and exterior applications. The product has been specially formulated for getting suitable balance of MFFT, flexibility, toughness and elongation. It is manufactured in state of the art plant with DCS control.

TYPICAL CHARACTERISTICS

1. Appearance	:	Milky White Pourable Liquid
2. Emulsifying System	:	Synthetic anionic
3. % Total solids	:	50 ± 1.0
4. pH at 25°C	:	8.5 ± 0.5
5. Brookfield viscosity LVF (CPS) SP. 2, 12 RPM at 25°C.	:	1000 max.
7. Compatibility with Fillers	:	Good
8. Film Appearance	:	Clear & Transparent
9. Particle size in micron	:	0.15 to 0.19
10. MFFT in °C	:	+20

ADVANTAGES IN USING APCOTEX AC 2550

- Good adhesion to masonry, cementitious surfaces.
- Better mechanical stability for high speed mixing.
- Superior water and alkali resistance.
- Fast drying with minimum odour.
- Dry film is tough and resistant to dirt pick up.
- Dispersion provides high degree of crack resistance and crack bridging properties.
- Good colour and colour retention.
- Suitable for latex floor paints and quality exterior semi-gloss trim.
- Excellent storage stability of formulated paints.

These suggestions and data are based on information, which we believe to be reliable. They are given for information only and in good faith, but conditions and methods of use of our products are beyond our control. We recommend that the user determine the suitability of our materials and suggestions before using them on a commercial scale.