



apcotex industries limited

AN ISO 9001: 2008 COMPANY

APCOTEX PT 500

APCOTEX PT 500 is a specialty Carboxylated Styrene–Butadiene latex developed for coating Art and Chromo papers.

It is manufactured by employing state-of-the-art emulsion polymerization technology ensuring product consistency.

PRODUCT SPECIFICATION

PROPERTIES	SPECIFICATION
Appearance	Milky white pourable liquid
Emulsifying System	Synthetic anionic
Total Solids (%)	50.0 ± 1.0
pH at 25°C	6.5 ± 0.5
Brookfield Viscosity LVF (CPS) SP.1,12 RPM at 25°C	500 max
Surface Tension (Dynes/cm) at 25°C	43.0 ± 3.0
Film Characteristics	Clear and Non tacky
Compatibility	Compatible with other coating colour substances

Advantages with Apcotex PT 500:

- Provides high wet and dry binding strength
- Provides high sheet gloss and print gloss
- Good runnability at high machine speeds
- Provides excellent coverage and coating holdout
- Suitable for blade and bar coaters

Storage Recommendation:

Store between temperatures of +5°C and 40°C. Keep containers closed when not in use. Protect from freezing and direct exposure to sunlight.

These suggestions and data are based on information that we believe to be reliable. They are given for information only and in good faith, but conditions and methods of use of our products are beyond our control. We recommend that the user determine the suitability of our materials and suggestions before using them on a commercial scale.