



apcotex industries limited

AN ISO 9001: 2008 COMPANY

APCOTEX SR 563

APCOTEX SR 563 is self-reinforcing Styrene Butadiene Rubber, commonly known as High Styrene Rubber. This is useful in rubber products to obtain optimal balance of high hardness, abrasion resistance, flex and other mechanical properties at low specific gravity.

Apcotex SR 563 is available in ready to use crumb form. This makes it easy to handle without the need to cut into small pieces, saving handling cost and power. The crumb form also enables easy processing in Open Mill or Internal Mixers.

Applications:

- Hawai Chappal
- Micro Cellular Solings
- Other products which require high hardness and abrasion resistance like moulded floor tiles, battery boxes, etc.

PRODUCT PROPERTIES

PROPERTY	SPECIFICATION
Physical Form	White Crumbs
Moisture content (%)	1.0 Max.
Ash content (%)	0.5 Max.
Organic acid content (%)	4 - 7
Stabilizer	Non Staining
Emulsifier	Mixed soap of rosin acid & fatty acid
Bound Styrene content (%)	63

Packaging:

Apcotex SR 563 is available in 25 Kgs HDPE Bags

Storage Recommendation:

Apcotex SR 563 should be kept in a covered area and away from direct sunlight.

These suggestions and data are based on information, which we believe to be reliable. They are given for information only and in good faith, but without guarantee, as condition and methods of use of our products are beyond our control. We recommend that the user determine the suitability of our materials and suggestions before adopting them on commercial scale.