



apcotex industries limited

AN ISO 9001: 2008 COMPANY

APCOTEX TSN 200

Apcotex TSN 200 is a specialty Styrene Butadiene Latex with improved flexibility and used as an admixture in cement mortar and concrete.

It is manufactured by employing state-of-the-art emulsion polymerization technology ensuring product consistency.

PRODUCT SPECIFICATION

PROPERTIES	SPECIFICATION
Appearance	Milky white pourable liquid
Emulsifying System	Synthetic anionic and nonionic
Total Solids (%)	50.5 \pm 0.5
pH at 25°C	9.5 \pm 0.5
Brookfield Viscosity LVF (CPS) SP.1,12 RPM at 25°C	250 max
Surface Tension (Dynes/cm) at 25°C	40.0 \pm 5.0
Specific Gravity	1.017 \pm 0.005
Dilutability with water	Dilutable in any proportion
Compatibility	Compatible with Cement and Concrete mixture

Advantages with Apcotex TSN 200:

- High resistance to water penetration
- Imparts excellent flexibility
- Enhances bonding between old and new concrete
- Offers good workability at reduced water/ cement ratio
- Mixes can be applied in thinner sections
- Improves abrasion resistance

Storage Recommendation:

Store between temperatures of +5°C and 40°C. Keep containers closed when not in use. Protect from freezing and direct exposure to sunlight.

These suggestions and data are based on information that we believe to be reliable. They are given for information only and in good faith, but conditions and methods of use of our products are beyond our control. We recommend that the user determine the suitability of our materials and suggestions before using them on a commercial scale.